

Smart Bracket Instructions

Step 1: Separate the bracket base from the adapter by sliding the adapter in one direction (see picture at side)

NOTE: With the Master label facing you, push the adapter body to the right.

Step 2: Remove the screws from the adapter base (see picture at side) and use appropriate adapter for your cable or u-bar lock

NOTE:

Small adapter for cable and u-locks: Range is from 6mm - 12 mm
 Large adapter for cable and u-locks: Range is from 12mm - 20mm
 (see picture at right for picture of bracket sizes)

Step 3: Place the lock inside the adapter and tighten the screws.

> For cable locks, place the adapter as close to the lock body as possible, then tighten the screws

> For U-locks, place the adapter on the shackle, as close to the cross-bar as possible, then tighten the screws

Set aside.

Step 4: Place the bracket base on the bicycle frame and loop the straps around the bike frame, inserting the ends of the straps into the screw slots.

Step 5: Tighten the base screws in the bicycle base with a flat-head screwdriver.

WARNING: Make sure to loop the bracket base underneath any wires on the bike frame.

Step 6: Cut the excess strap, making sure the base is secure

Step 7: To attach the adapter with the Cable/ U-lock to the bracket base, simply slide the adapter all the way onto or off the bracket base until you feel a slight catch

Note: There are a number of positions that the bike lock bracket can be positioned on the frame. Two are shown here.

Step 1
Overhead
View



Step 1
Side View



Step 2
Underneath
View



Step 2
Side View



Step 3
Cable Locks



small adapter large adapter

Step 3
U-bars



Step 4
Place bracket
on frame



Step 5
Tighten
screws



Step 7
U-bar Locks



Step 7
Cable Locks

